


(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
2 March 2006 (02.03.2006)

PCT

(10) International Publication Number
WO 2006/021812 A1

- (51) International Patent Classification⁷: **F16B 5/02**, (74) Agent: **BAE SYSTEMS plc, Group IP Dept**; P.O. Box 87, Lancaster House, Farnborough Aerospace Centre, Farnborough Hampshire GU14 6YU (GB).
- (21) International Application Number: **PCT/GB2005/050102**
- (22) International Filing Date: **5 July 2005 (05.07.2005)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
04254144.1 9 July 2004 (09.07.2004) EP
0415399.5 9 July 2004 (09.07.2004) GB
- (71) Applicant (for all designated States except US): **BAE SYSTEMS PLC [GB/GB]**; 6 Carlton Gardens, London Greater London SW1Y 5AD (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **WOOD, Christopher Nell [GB/GB]**; BAE SYSTEMS Aircraft Services Group, Woodford Aerodrome Chester Road, Woodford Cheshire SK7 1QR (GB). **ROBINSON, Phillip Ian [GB/GB]**; BAE SYSTEMS Aircraft Services Group, Woodford Aerodrome Chester Road, Woodford Cheshire SK7 1QR (GB). **APPS, Howard Raymond [GB/GB]**; BAE SYSTEMS Aircraft Services Group, Woodford Aerodrome Chester Road, Woodford Cheshire SK7 1QR (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FASTENER ARRANGEMENT FOR FASTENING A DETACHABLE PANEL



(57) Abstract: In one embodiment the fastening of a detachable panel can be seen in, an assembly comprising a fastener (28), a panel (10) and a supporting structure (12). The panel (10) and a flange (14) of the supporting structure (12) are formed with respective tapered holes (22, 24) which receive the fastener (28), the taper of one hole being a continuation of the taper of the other. The fastener (28) is secured to the flange (12) and urges a tapered surface (32) of the fastener (28) into the tapered holes (22, 24) in a non-jamming manner thereby locating the panel (10) with respect to the flange (12) and hence with respect to the supporting structure (14).

- 1 -

Fastener Arrangement for Fastening a Detachable Panel

The invention relates to fastening a detachable panel and is particularly, but not exclusively, concerned with the fastening of a detachable load bearing panel to the supporting structure of an aircraft.

5 Panels on an aircraft, such as engine cover panels, need to be detached at times for access to working parts of the aircraft. Large panels can often be fastened down by a multiplicity of fasteners. Whilst removal of the fasteners for detachment of the panel is usually not too difficult, re-alignment of the panel, during re-fitting, to clear the fasteners protruding from the supporting structure
10 can sometimes be a problem where large numbers of fasteners are involved.

It is known to attach a panel to an aircraft structure using a multiplicity of fasteners, e.g. studs attached to the structure and which project out of the structure for location in fixing holes in the panel. Once located in the panel, nuts are screwed on to the studs to hold the panel in place. Detachment of the panel
15 is not difficult with such an arrangement but re-location of the panel can be difficult as it is necessary to align the studs with the large number of holes in the panel. Another problem with such an arrangement can arise during the initial installation of the studs where it is necessary to ensure that all the studs are precisely parallel with each other. This can be quite difficult to achieve where
20 the panel and structure have compound curvatures, and can require the use of expensive tooling to ensure that the studs are installed correctly.

An object of the present invention is to provide a fastening which will help to overcome the problems outlined in the immediately preceding paragraph and which may also be useful in other applications where detachable fastening of
25 panels is involved.

According to a first aspect of the invention there is provided an assembly comprising a fastener, a panel and a supporting structure to which the panel is detachably fastened by the fastener, the panel and supporting structure being formed with tapered holes which receive the fastener, the taper of one hole
30 being a continuation of the taper of the other, and the fastener urging a tapered

- 2 -

surface into the tapered holes in a non-jamming manner thereby locating the panel with respect to the supporting structure.

This arrangement provides advantages over the prior art in respect of maintaining a shear load path through the panel and the fastener which deviates from the plane of the panel by a lesser amount. A second advantage is that the joint can be disassembled more easily because the interference fit of the prior art taper is avoided.

Where the panel of the assembly needs to be held in place by a multiplicity of fasteners, the fasteners can be located one at a time in such an assembly making it unnecessary to align a multiplicity of bolts on the structure with holes in the panel. At the same time, the tapers ensure accurate location of the panel with respect to the mounting structure.

For aerodynamic surfaces, for example, the fastener is positioned in the holes so as not to project beyond an outer surface of the panel. Such positioning of the fastener means that it will not interfere with air flow over the panel.

In one embodiment, the tapered surface may be formed on the fastener itself.

In another embodiment, the tapered surface may be formed on a separate element which locates in the tapered holes and through which the fastener passes to hold the element in place.

According to a second aspect of the invention there is provided a fastener for fastening a detachable panel to a supporting structure, the panel and supporting structure being formed with tapered holes which receive the fastener, the taper of one hole being a continuation of the taper in the other, the fastener comprising a body having a tapered outer surface which, in use, locates in the tapered holes in a non-jamming manner and thereby positions the panel with respect to the supporting structure.

The taper on the fastener is of a non-jamming type, for example having a taper angle greater than around 5° degrees. By selecting a non jamming taper

- 3 -

angle, it is possible to rotate the fastener in the hole to secure it in position. For example, the fastener may have a screw threaded end which screws into a nut, such as an anchor nut, on the supporting structure.

According to a third aspect of the invention there is provided a fastening
5 means for fastening a detachable panel to a supporting structure, the fastening means comprising a tapered element and a fastener, the panel and supporting structure being formed with tapered holes which receive the tapered element and the fastener, the taper of one hole being a continuation of the taper in the other, the tapered element comprising a body having a tapered outer surface
10 and having a bore through which the fastener can be passed to secure the tapered element in the tapered holes and thereby position the panel with respect to the supporting structure.

Where a tapered element of the kind set out in the immediately preceding paragraph is used, the fastener preferably takes the form of a simple
15 bolt which passes through the tapered element leading to a reduction in the cost of the fastener.

The tapered element may be of frusto-conical form.

Fastening of detachable panels will now be described by way of example with reference to the accompanying drawings in which:

20 Fig 1 is a cross-section through a panel and supporting structure illustrating one form of fastening using a fastener having a tapered surface and

Fig 2 is a cross-section through a panel and supporting structure illustrating another form of fastening using a tapered element and a fastener of standard kind.

25 Looking at Fig 1, a panel 10 is fastened to a supporting structure 12 which in the embodiment illustrated has a stepped-down flange 14 which creates a recess 16. The recess 16 receives the panel 10 so that an outer surface 18 of the panel lies flush with an adjacent outer surface 20 of the supporting structure 12.

- 4 -

With the panel 10 held against the flange 14, a drill bit is used to drill straight through the panel 10 and flange 14 to enable a taper cutting tool (not shown) of known kind to be inserted. The taper cutting tool is then used to produce respective tapered holes 22, 24 in the panel 10 and flange 14 simultaneously from the straight drilling. An adjustable depth control surrounds the taper cutting tool and is adjusted to ensure the correct depth of cut. It will be seen clearly in Fig 1 that the taper of the hole 24 forms a continuation of the taper of the hole 22. It will also be seen in Fig 1 that hole 24 is tapered for its full depth. Although a full depth taper is preferred, the hole 24 could be tapered for, say, two thirds of its depth leaving the remainder of the hole in its straight drilled form. A floating anchor nut 26 of known kind is fastened to the underside of the flange 14 in alignment with the hole 24. Several such holes 22, 24 are formed in the panel 10 and flange 14 at spaced apart positions.

A fastener 28 has a body 30 formed with a tapered outer surface 32. The angle of taper X of the body 30 corresponds to the angle of taper of the holes 22, 24. The body 30 is formed with a screw-threaded lower end 34 as viewed in Fig 1 which screws into the anchor nut 24 and has a recess 36 in a flat upper end 38 suitable for receiving a torque applying tool (not shown). It will be noted from Fig 1 that the tapered part of the fastener body 30 has an axial length substantially equal to the combined thicknesses of the panel 10 and flange 14. The torque applying tool is used to turn the fastener 28 in the holes 22, 24 so that the screw-threaded lower end 34 screws into the anchor nut 26. Turning is continued until the tapered outer surface 32 of the fastener 28 is driven firmly into contact with the walls of tapered holes 22, 24. At that point, the flat upper end 38 of the fastener 28 will lie flush with the surrounding outer surface 18 of the panel 10. By ensuring that the upper end 38 of the fastener does not project above the surface 18, it will not interfere with air flow over the surface 18 where the panel 10 forms part of an aircraft outer skin. The location of the tapered fastener 28 in the tapered holes 22, 24 ensures that the panel 10 will be located accurately in relation to the flange 14. Further fasteners 28 are screwed in remaining holes to fasten the panel 10 in place.

- 5 -

As the fastener 28 has to be rotated in the holes 22, 24 to screw it into position, the angle of taper X is selected so as to be non-jamming. A typical example of a jamming taper is a Morse taper drill where the taper permits the drill to be driven by friction. In the present invention, the angle of taper X must not be too small so as to produce a jamming effect which would prevent rotation of the fastener 28. On the other hand, the angle of taper X must not be so great that accurate positioning of the panel 10 relative to the flange 14 will be impaired. With that in mind, we use an angle X in the range of 5° to 45° degrees and have found an angle of approximately 30° degrees to be particularly suitable. The angle X chosen will of course be partly dependent on the materials chosen as the frictional characteristics operating between different materials will vary.

The angle chosen will alter the shear and clamping qualities of the joint. If a larger angle is chosen the clamping effect will be enhanced but the ability to transfer shear load will be reduced. If a smaller angle is chosen the shear load transfer quality of the joint will be enhanced but the clamping will be reduced. If too great an angle is selected a phenomenon known as "edge distress" may occur. With such a design the outer edge region of the fastener may become unacceptably thin and subject to distortion.

To detach the panel 10 from the supporting structure 12, the fasteners 28 are unscrewed from the anchor nuts 26 and simply lifted out of the holes 22, 24. The panel 10 can then be lifted off the flange 14.

Looking next at Fig 2, parts corresponding to parts shown in Fig 1 carry the same reference numerals and only the differences will be described.

Instead of using a specially manufactured tapered screw threaded fastener, the embodiment in Fig 2 uses a frusto-conical element 40 having a coaxial hole 42 through which a standard bolt 44 passes. The element 40 has an outer surface 47 tapered to correspond with the angle of taper of the holes 22, 24 and preferably tapers substantially to nothing at its lower end as viewed in Fig 2. The length of the tapered element 40 is such as to enable the top of a head 46 of the bolt 44 to lie flush with the surface 18 of the panel. Where the

- 6 -

panel 10 forms part of an aircraft outer skin, filler (not shown) may be used to fill the space between the bolt head 46 and the adjacent wall of hole 22. The angle of taper X is preferably selected in Fig 2 to be non-jamming so that the tapered element 40 can easily be removed from the holes 22, 24 when the
5 panel 10 is to be detached. However, it will be appreciated that it is not necessary to facilitate rotation of the tapered element 40 in the holes 22, 24 when fastening it into position.

The use of the tapered fastener 28 or the tapered element 40 provides a good shear resistant connection between the panel 10 and the supporting
10 structure 12 as well as good clamping. It is not necessary to produce a recess in the outer surface of the panel specifically to receive a nut as is the case with the upstanding bolt arrangement referred to in the introduction. Moreover parallelism is not a critical issue as the fasteners can simply be inserted one at a time and, therefore, it is not necessary to align a large number of holes in a
15 panel with permanently fixed fasteners. A more direct load path is also provided by the present invention compared to that provided by the upstanding bolt arrangement owing to the overall "depth" of the joint being lower, which reduces the out of plane deflection of the load path.

- 7 -

Claims

- 1 An assembly comprising a fastener, a panel and a supporting structure to which the panel is detachably fastened by the fastener, the panel and supporting structure being formed with tapered holes which receive the
- 5 fastener, the taper of one hole being a continuation of the taper of the other, and the fastener urging a tapered surface into the tapered holes in a non-jamming manner thereby locating the panel with respect to the supporting structure.
- 10 2 An assembly according to claim 1 in which the fastener is positioned in the holes so as not to project beyond an external surface of the panel.
- 3 An assembly according to claim 1 or 2 in which the tapered surface is formed on the fastener itself.
- 15 4 An assembly according to claim 1 in which the tapered surface is formed on an element located in the tapered holes, and the fastener passing through the element to hold the element in place.
- 20 5 An assembly according to claim 4 in which the element is of frusto-conical form.
- 6 An assembly according to any preceding claim in which the angle of taper of the holes and the angle of taper of the said tapered surface are the
- 25 same.
- 7 An assembly according to any preceding claim in which the angle of taper of the said tapered surface is in the range of 5° to 45° degrees.

- 8 -

8 An assembly according to claim 7 in which the angle of taper is substantially 30 degrees.

5 9 An assembly comprising a fastener, a panel and a supporting structure, the assembly being constructed and arranged substantially as described herein with reference to the accompanying drawings.

10 10 A fastener for fastening a detachable panel to a supporting structure, the panel and supporting structure being formed with tapered holes which receive the fastener, the taper of one hole being a continuation of the taper in the other, the fastener comprising a body having a tapered outer surface which is arranged to locate in the tapered holes in a non-jamming manner and thereby position the panel with respect to the supporting structure.

15

11 A fastener for fastening a detachable panel to a supporting structure, the fastener being constructed and arranged substantially as described herein with reference to the accompanying drawings.

20 12 An fastening means for fastening a detachable panel to a supporting structure, the fastening means comprising a tapered element and a fastener, the panel and supporting structure being formed with tapered holes which receive the tapered element and the fastener, the taper of one hole being a continuation of the taper in the other, the tapered element comprising a body
25 having a tapered outer surface and having a bore through which the fastener can be passed to secure the tapered element in the tapered holes and thereby position the panel with respect to the supporting structure.

- 9 -

13 A fastening means for fastening a detachable panel to a supporting structure, the fastening means being constructed and arranged substantially as described herein with reference to the accompanying drawings.

INTERNATIONAL SEARCH REPORT

Application No

PCT/GB2005/050102

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 F16B5/02 B64C1/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16B B64C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 921 364 A (BRILES FRANKLIN S) 25 November 1975 (1975-11-25) the whole document	1-13
A	GB 1 341 459 A (SIMMONDS SA) 19 December 1973 (1973-12-19) figures 1a,2a	1-13
A	US 3 742 584 A (MARCOUX A ET AL) 3 July 1973 (1973-07-03) the whole document	1-13
A	US 4 974 989 A (SALTER LARRY) 4 December 1990 (1990-12-04) the whole document	1-13
A	US 3 304 109 A (SCHUSTER MICHAEL M) 14 February 1967 (1967-02-14) the whole document	1-13

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

9 September 2005

Date of mailing of the international search report

27/09/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Huusom, C

INTERNATIONAL SEARCH REPORT

Information on patent family members

Application No

PCT/GB2005/050102

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 3921364	A	25-11-1975	US 3849964 A DE 2439377 A1 FR 2241015 A1 GB 1449307 A JP 50049541 A	26-11-1974 27-02-1975 14-03-1975 15-09-1976 02-05-1975
GB 1341459	A	19-12-1973	FR 2119873 A1 DE 2160422 A1	11-08-1972 27-07-1972
US 3742584	A	03-07-1973	NONE	
US 4974989	A	04-12-1990	DE 3430914 A1 DK 398784 A ,B, ES 296385 U ES 8701319 A1 FR 2551147 A1 GB 2145492 A ,B IL 72698 A IT 1199598 B JP 1616810 C JP 2040122 B JP 60060313 A NO 843288 A ,B, SE 459272 B SE 8404150 A US 4702658 A	14-03-1985 23-02-1985 01-11-1987 16-02-1987 01-03-1985 27-03-1985 31-01-1991 30-12-1988 30-08-1991 10-09-1990 06-04-1985 25-02-1985 19-06-1989 23-02-1985 27-10-1987
US 3304109	A	14-02-1967	NONE	